



Unit Number	Bearing Number	Shaft Size	D Dimension	B Dimension	C Dimension	Basic Load	
						Ratings	
						Cr	Cor
SSCSB201	SSCSB201	12 mm	40.0 mm 1.575 in	22.0 mm 0.866 in	12.0 mm 0.472 in	9.55 kN 21.1 lb	4.80 kN 10.6 lb
SSCSB201-8	SSCSB201-8	1/2 in	40.0 mm 1.575 in	22.0 mm 0.866 in	12.0 mm 0.472 in	9.55 kN 21.1 lb	4.80 kN 10.6 lb
SSCSB202	SSCSB202	15 mm	40.0 mm 1.575 in	22.0 mm 0.866 in	12.0 mm 0.472 in	9.55 kN 21.1 lb	4.80 kN 10.6 lb
SSCSB202-10	SSCSB202-10	5/8 in	40.0 mm 1.575 in	22.0 mm 0.866 in	12.0 mm 0.472 in	9.55 kN 21.1 lb	4.80 kN 10.6 lb
SSCSB203	SSCSB203	17 mm	40.0 mm 1.575 in	22.0 mm 0.866 in	12.0 mm 0.472 in	9.55 kN 21.1 lb	4.80 kN 10.6 lb
SSCSB204-12	SSCSB204-12	3/4 in	47.0 mm 1.850 in	25.0 mm 0.984 in	14.0 mm 0.551 in	12.8 kN 28.2 lb	6.65 kN 14.7 lb
SSCSB204	SSCSB204	20 mm	47.0 mm 1.850 in	25.0 mm 0.984 in	14.0 mm 0.551 in	12.8 kN 28.2 lb	6.65 kN 14.7 lb
SSCSB205-14	SSCSB205-14	7/8 in	52.0 mm 2.047 in	27.0 mm 1.063 in	15.0 mm 0.591 in	14.0 kN 30.9 lb	7.85 kN 17.3 lb
SSCSB205-15	SSCSB205-15	15/16 in	52.0 mm 2.047 in	27.0 mm 1.063 in	15.0 mm 0.591 in	14.0 kN 30.9 lb	7.85 kN 17.3 lb
SSCSB205	SSCSB205	25 mm	52.0 mm 2.047 in	27.0 mm 1.063 in	15.0 mm 0.591 in	14.0 kN 30.9 lb	7.85 kN 17.3 lb
SSCSB205-16	SSCSB205-16	1 in	52.0 mm 2.047 in	27.0 mm 1.063 in	15.0 mm 0.591 in	14.0 kN 30.9 lb	7.85 kN 17.3 lb
SSCSB206-18	SSCSB206-18	1-1/8 in	62.0 mm 2.441 in	30.0 mm 1.181 in	16.0 mm 0.630 in	19.5 kN 43 lb	11.3 kN 24.9 lb
SSCSB206	SSCSB206	30 mm	62.0 mm 2.441 in	30.0 mm 1.181 in	16.0 mm 0.630 in	19.5 kN 43 lb	11.3 kN 24.9 lb
SSCSB206-19	SSCSB206-19	1-3/16 in	62.0 mm 2.441 in	30.0 mm 1.181 in	16.0 mm 0.630 in	19.5 kN 43 lb	11.3 kN 24.9 lb
SSCSB206-20	SSCSB206-20	1-1/4 in	62.0 mm 2.441 in	30.0 mm 1.181 in	16.0 mm 0.630 in	19.5 kN 43 lb	11.3 kN 24.9 lb
SSCSB207-20	SSCSB207-20	1-1/4 in	72.0 mm 2.835 in	32.0 mm 1.260 in	17.0 mm 0.669 in	25.7 kN 56.7 lb	15.4 kN 34 lb
SSCSB207-22	SSCSB207-22	1-3/8 in	72.0 mm 2.835 in	32.0 mm 1.260 in	17.0 mm 0.669 in	25.7 kN 56.7 lb	15.4 kN 34 lb
SSCSB207	SSCSB207	35 mm	72.0 mm 2.835 in	32.0 mm 1.260 in	17.0 mm 0.669 in	25.7 kN 56.7 lb	15.4 kN 34 lb
SSCSB207-23	SSCSB207-23	1-7/16 in	72.0 mm 2.835 in	32.0 mm 1.260 in	17.0 mm 0.669 in	25.7 kN 56.7 lb	15.4 kN 34 lb

SSCSB208-24	SSCSB208-24	1-1/2 in	80.0 mm 3.150 in	34.0 mm 1.339 in	18.0 mm 0.709 in	29.1 kN 64.2 lb	17.8 kN 39.2 lb
SSCSB208	SSCSB208	40 mm	80.0 mm 3.150 in	34.0 mm 1.339 in	18.0 mm 0.709 in	29.1 kN 64.2 lb	17.8 kN 39.2 lb